

# ELITE

- Hardwearing Vinyl Floor covering in elegant and realistic wood designs
- Excellent resistance to scratches, abrasion, soiling and staining.
- Ideal for showrooms, hotels and leisure environments

**APPLICATION :** Suitable for medium traffic areas like Shops, Showrooms, Hospitals, Schools, Offices, Hotels and Leisure environments.

### RESISTANCE TO CHEMICALS

Elite is normally resistant to mild diluted acids and alkalis. The surface must be cleaned immediately if concentrated acids or alkalis spill.



### INSTALLATION

- Ensure sub floors are smooth, dry, clean and structurally sound.
- We recommend Fevicol SR 998/SR 505 or any equivalent rubber based adhesive for laying.
- For a clean room condition, seam welding is recommended.
- To minimize the risk of shade variation in colours, do not mix batch numbers.

### MAINTENANCE TIPS

- Clean the surface daily with a damp mop and weekly or fortnightly with mild soap solution.
- To remove stubborn stains, use a coir brush or fine steel wool no. 000 soaked in warm soap solution to clean the affected area.
- Use water to remove chemical spillage on the flooring.
- Do not throw lighted cigarette butts or match sticks on the floor.

### Application

	Education	<input type="checkbox"/>
	Healthcare & Wet Area	<input type="checkbox"/>
	Residential	<input type="checkbox"/>
	Office Retail and Hospitality	<input type="checkbox"/>
	Transport	<input type="checkbox"/>

### Classification

	Commercial / Residential Use	22
	Industrial Use	
	Abrasion Resistance	Group T

### Technical Characteristics

	Total Thickness	1.5 +/- 0.130 mm
	Roll Width	2000 mm
	Roll Length	± 20 mtr.
	Total Weight	2.7 kg/m2

### Technical Performances

	Dimensional Stability	
	Residual Indentation	≤ 0.10 mm
	Castor Chair Continuous Use	Suitable
	Light Fastness	≥ 6
	Flexibility	Passes
	Resistance to Chemicals	Good resistance
	Slip Resistance	R 9
	Fungi & Bacterial Resistance	
	Electrical Resistance	
	Sound absorption	5 dB
	Under Floor Heating	Yes
	Reaction to Fire	B fl-s 1
	Body Voltage	≤ 2 kv
	Thermal Conductivity	0.25W/m-K



Authorised Dealer



ELITE



ELITE



# ELITE



Note: This card represents our standard shades but slight variation may occur



-  Residential
-  Office Retail
-  Hospitality
-  Healthcare
-  Education

